

APPLICATION FOR UNITED STATES PATENT

Inventor(s): Herbert Gropp  
Dietmar Klose  
Claus-Peter Dürlich  
Manfred Janssen

Invention: BUILT-UP CAMSHAFT

Attorney Docket Number: rum205

Horst M. Kasper, their attorney  
13 Forest Drive, Warren, N.J. 07059  
Telephone: (908)757-2839  
Telefax: (908)668-5262  
Reg.No. 28559; Docket No.: rum205SP

SPECIFICATION

09476521.010300

## BUILT-UP CAMSHAFT

## BACKGROUND OF THE INVENTION

## 1. Field of the Invention

The present invention relates to a built-up camshaft including a pipe or a solid rod, cams, ring bearings, end pieces, and other parts.

2. Brief Description of the Background of the  
Invention Including Prior Art

Built-up camshafts are produced today essentially by a partial internal high-pressure deformation of the pipe against the cams, by elevating, raising, and advancing the surface of the pipe and squeezing the cams onto the pipe or by shrink-fitting the cams on the pipe.

The shaping of the cams from the pipe by internal high-pressure deformation is also being considered.

However, all of these production methods are accompanied with substantial disadvantages. The starting materials have to exhibit very low tolerances in regard to dimension and material characteristics and the joining technique is complicated. The internal high-pressure deformation is expensive and produces thin walls at exactly the important tips of the cams.

## SUMMARY OF THE INVENTION

### 1. Purposes of the Invention

Based on the state of the art, the present invention has the object to build a camshaft with commercially available materials and semifinished materials with a simple technology, wherein said camshaft is manufactured in mass production at an advantageous cost.

These and other objects and advantages of the present invention will become evident from the description which follows.

### 2. Brief Description of the Invention

The present invention provides for a camshaft according to the characterizing portion of claim 1.

Suitable embodiments of the invention are contained in the subclaims.

The attachment of the cams and of the other parts on the pipe is performed with a longitudinal compression joint. The pipe is coated, preferably with a finely crystalline phosphate coating, as known from the East German printed patent document 015 2972, such that the overdimensioned cams, which are to be slipped, do not score and seize, that the friction tightness is increased, and that no tribocorrosion is generated later on. Following a careful

09476521-010300

VL  
10/20/00  
Considered



Instead of the finely crystalline phosphate coating, it is also possible to use other surface coatings, such as metal and cement. In the case of cement, the formation of the front face to be slid on is of importance for the distribution of the adhesive on the pipe or the solid rod.

The cams are appropriately formed of light-weight sheet metal construction, such as is for example known from the German printed patent document 196 40 872.5. The cams can however also be made of solid material, plastic or ceramic material. A drawn surface quality is sufficient for the pipe and also for the bearing seats. However, a regrinding of the bearing positions can be required for tolerance reasons.

In the accompanying drawings, in which are shown several of the various possible embodiments of the present invention:

- 5 -

camshaft segment;

Fig. 2 is a schematic sectional view through a camshaft end;

Fig. 3 is a view of the entire camshaft on a reduced scale.

#### DESCRIPTION OF INVENTION AND PREFERRED EMBODIMENT

The jointing coating 2 between the pipe 1 and the cams 3 of light-weight sheet metal construction is indicated in Fig. 1. <sup>B1</sup> However, the jointing coating 2 in fact does not have a measurable radial extension. <sup>B2</sup>

In Fig. 2, the pipe has an inner coating 5, such that the end pieces <sup>4</sup> <sup>and 7</sup> can be pressed in.

Fig. 3 shows the ~~entire camshaft, wherein all parts~~ <sup>B3</sup> ~~to be disposed on the pipe, are~~ longitudinally pressed onto the camshaft. For simplicity's sake, the cams are represented as disks.